



STRESS RELIEVING MACHINE (SR MACHINE) AND ACCESSORIES



Features:

- High Voltage SR Panel
- Available in 30A, 60A, 100A Output
- 3 & 6 Channel Options
- PID Control and Manual Operations
- Useful in Heat Treatment up to 1200 Degree Celsius
- Robust Construction
- Retransmission OR Auto Design Available



Address: C56, Gala no 210, 2nd Floor, Turbhe industrial park, Turbhe, Navi Mumbai,
Maharashtra, India, 400705

Email: info@ndtmasters.com / mfeep1@gmail.com Contact: +91 9594018506 / +91 8779124655

➤ Automatic machine with 3PIDs and 3 channels:

Models (3 Channel)	Input Supply	Output Supply
MF-SR-30A-3	415 V 32 Amps 3 Phase 50 Hz	230V x 32 Amps 3 Phase x 3 Channels
MF-SR-60A-3	415 V 63 Amps 3 Phase 50 Hz	230V x 63 Amps 3 Phase x 3 Channels
MF-SR-100A-3	415 V 100 Amps 3 Phase 50 Hz	230V x 100 Amps 3 Phase x 3 Channels

➤ Automatic machine with 6 PIDs and 6 channels:

Models (6 Channel)	Input Supply	Output Supply
MF-SR-30A-6	415 V 32 Amps 3 Phase 50 Hz	230V x 32 Amps 3 Phase x 6 Channels
MF-SR-60A-6	415 V 63 Amps 3 Phase 50 Hz	230V x 63 Amps 3 Phase x 6 Channels
MF-SR-100A-6	415 V 100 Amps 3 Phase 50 Hz	230V x 100 Amps 3 Phase x 6 Channels

SR Accessories:



Thermocouple attachment unit is used to attach thermocouple wire On ferromagnetic job. It comes with Magnet and Clip for attachment.



It is required to produce chart for Post weld heat treatment in graphical representation. It also comes with the option of digital temperature indicator.

Other Accessories:

Nichrome wire, Ceramic Beads, 'K' Type Thermocouple wire, Compensation cable, Insulation Glass wool, power cables.